

Plateau Head Knob-type Selector Switch

Easy connector enables less assembly and less wiring

- 50 mm body length.
- Highly reliable Major Omron basic switch, SS model built in.
- Possible cross over wiring on circuit construction.
- Easy one push to connect the Operation and Switch Units.



Ordering Information

Туре	No. of notches	Reset method	Output	Model	Selector color
Plateau Head Knob-type Selector Switch	2 Notches	Automatic	SPDT	A3US-SB-2M-AC	Black

Specifications

Approved Standard Ratings

Certification Authority UL (See Note: 1 and Note: 2)		TÜV (See Note: 3)
Certification no. UL508 CSA C22.2 No.14		EN60947-5-1
Rating	30 VDC 0.1 A	12 30 VDC 0.1 A
File no.	E41515	J50236157

Note: 1. Only Switch Blocks are recognized by UL. (Surrounding air Temperature: 55 °C)

Note: 2. Please use the power supply specified in UL class 2.

Note: 3. Use 4A 250V as short-circuit protective device when using under EN authorized rating standard (IEC60127-2 SS1).

Ratings

Contacts 30 VDC, 0.1 A (Resistive load) Minimum applicable load: 1 mA at 5 VDC Rated values are obtained from tests conducted under the following conditions.

- 1. Load: Resistive load
- 2. Mounting conditions: No vibration and no shock
- 3. Temperature: 20 \pm 2 °C
- 4. Operating frequency: 20 operations/min


Characteristics

Allowable operating frequency Electrical 30 operations/minute max.		Item	Knob-type Selector Switch		
Insulation resistance 100 MΩ min. (at 500 VDC)	operating		30 operations/minute max.		
Contact resistance 250 mΩ max. (initial value) Dielectric strength Between terminals of same polarity 500 VAC, 50/60 Hz for 1 minute Vibration resistance Malfunction 1,500 VAC, 50/60 Hz for 1 minute Shock resistance Malfunction 300 m/s² Hz, 1.5-mm double amplitude (malfunction within 1 ms) Shock resistance Malfunction 300 m/s² max. (malfunction within 1 ms) Durability Mechanical Electrical 250,000 operations min. Connector holding force 40 N max. Rated insulation voltage (Ui) 30 V (EN60947-5-1) Electric shock protection class Class II Degree of contamination 3 (EN60947-5-1) Impulse withstand voltage Between terminals of different polarity Between each terminal and ground 800 V (EN60947-5-1) Conditional short-circuit current 100 A (EN60947-5-1) Conventional enclosed thermal current (Ithe) 0.1 A (EN60947-5-1) Weight Approx. 30 g			30 operations/minute max.		
Dielectric strength Between terminals of same polarity Between each terminaland ground Vibration resistance Malfunction Malfunction Mechanical Electrical Connector holding force Rated insulation voltage (Ui) Electric shock protection class Degree of contamination Between terminals of different polarity Between each terminal and ground Conditional short-circuit current Conventional Conventio	Insulation resistance		100 MΩ min. (at 500 VDC)		
Dielectric strength Between each terminal and ground Vibration resistance Malfunction Mechanical 250,000 operations min. 40 N max. Class II Degree of contamination Class II Degree of contamination Malfunction Mechanical Class II Malfunction Mechanical Malfunction Mechanical Class II Mechanical Mechanical Malfunction Mechanical Malfunction Malf	Contact res	istance	250 mΩ max. (initial value)		
Vibration resistance Malfunction Mechanical 250,000 operations min. 100,000 operations min. Connector holding force 40 N max. Class II Degree of contamination Class II Degree of contamination Malfunction Mechanical 250,000 operations min. Class II 30 V (EN60947-5-1) Between terminals of same polarity Between terminals of different polarity Between terminals of different polarity Between each terminal and ground Conditional short-circuit current Conventional enclosed thermal current (Ithe) Meight Approx. 30 g	Dielectric		500 VAC, 50/60 Hz for 1 minute		
resistance Malfunction (malfunction within 1 ms) Shock resistance Malfunction 300 m/s² max. (malfunction within 1 ms)	strength		1,500 VAC, 50/60 Hz for 1 minute		
resistance Malfunction 300 m/s² max. (malfunction within 1 ms Mechanical 250,000 operations min. 100,000 operations min. 100,000 operations min. 40 N max. Rated insulation voltage (Ui) 30 V (EN60947-5-1) Electric shock protection class Class II Degree of contamination 3 (EN60947-5-1) Impulse withstand voltage Between terminals of same polarity Between each terminal and ground Conditional short-circuit current Conventional enclosed thermal current (Ithe) Weight Mechanical 250,000 operations min. 100,000 operations min. 20 (EN60947-5-1) 800 V (EN60947-5-1) 800 V (EN60947-5-1) 800 V (EN60947-5-1)		Malfunction			
Durability Electrical 100,000 operations min.		Malfunction	300 m/s ² max. (malfunction within 1 ms)		
Connector holding force 40 N max. Rated insulation voltage (Ui) 30 V (EN60947-5-1) Electric shock protection class Class II Degree of contamination 3 (EN60947-5-1) Impulse withstand voltage Withstand voltage Between terminals of different polarity Between each terminal and ground Conditional short-circuit current 100 A (EN60947-5-1) Conventional enclosed thermal current (Ithe) Weight Approx. 30 g	Durability	Mechanical	250,000 operations min.		
Rated insulation voltage (Ui) Electric shock protection class Degree of contamination Between terminals of same polarity Between terminals of different polarity Between each terminal and ground Conditional short-circuit current Conventional enclosed thermal current (Ithe) Weight Class II 3 (EN60947-5-1) 800 V (EN60947-5-1) 800 V (EN60947-5-1) 0.1 A (EN60947-5-1) Approx. 30 g	Electrical		100,000 operations min.		
Electric shock protection class Degree of contamination Between terminals of same polarity Between terminals of different polarity Between each terminal and ground Conditional short-circuit current Conventional enclosed thermal current (lthe) Weight Class II 800 V (EN60947-5-1)	Connector holding force		40 N max.		
Degree of contamination Impulse withstand voltage Conditional short-circuit current Conventional enclosed thermal current (Ithe) Between terminals of same polarity Between terminals of different polarity Between each terminal and ground 100 A (EN60947-5-1) 0.1 A (EN60947-5-1) Approx. 30 g	Rated insulation voltage (Ui)		30 V (EN60947-5-1)		
Impulse withstand voltage Between terminals of same polarity Between terminals of different polarity Between each terminal and ground Conditional short-circuit current Conventional enclosed thermal current (Ithe) Weight Between terminals of 800 V (EN60947-5-1)	Electric shock protection class		Class II		
Impulse withstand voltage Conditional short-circuit current Conventional enclosed thermal current (lthe) Same polarity Between terminals of different polarity Between each terminal and ground 100 A (EN60947-5-1) 0.1 A (EN60947-5-1) Approx. 30 g	Degree of contamination		3 (EN60947-5-1)		
Conventional enclosed thermal current (Ithe) 0.1 A (EN60947-5-1) Weight Approx. 30 g	Impulse withstand voltage same polarity Between terminals of different polarity Between each		800 V (EN60947-5-1)		
thermal current (Ithe) 0.1 A (EN60947-5-1) Weight Approx. 30 g	Conditional	short-circuit current	100 A (EN60947-5-1)		
			0.1 A (EN60947-5-1)		
Degree of protection IP40	Weight		Approx. 30 g		
	Degree of protection		IP40		
Ambient operating temperature -20 °C to 70 °C (with no icing or condensation)	Ambient operating temperature				
Ambient operating humidity 35 % to 85 % RH	Ambient operating humidity		35 % to 85 % RH		
Ambient storage temperature -40 °C to 70 °C (with no icing or condensation)	Ambient storage temperature				
Ambient storage humidity 35 % to 85 % RH	Ambient storage humidity		35 % to 85 % RH		


Operating Characteristics

Features	A3US
Total travel force (TTF) max.	0.34 N·m
Resetting force (RF) max.	0.34 N·m
Total travel (TT)	Approx. 90 °

Circuit Diagram



Dimensions (unit: mm)



Safety Precautions

Refer to Safety Precautions for All Pushbutton Switches/Indicators.

Precautions for Safe Use


- Do not disassemble or modify the Switch under any circumstances. Doing so may cause malfunction.
- Do not drop or subject the Switch to extreme shock or force. This may prevent the Switch from functioning to its full capability.
- The durability of the Switch varies considerably depending on the switching conditions. Always test the switch under actual working conditions before application and use the Switch only for the number of switching operations allowed.
- Do not allow the load current to exceed the rated value. This may damage or burn out the Switch.
- Refer to the Circuit Diagram and make sure to wire correctly. Only the terminal (1) is printed and the right end of the terminal is read

The switch back Terminal (1)

- Do not use the Switch in locations where explosive or flammable gases or liquid may be present or scattered. The electric ark or the heat caused by switching contacts may trigger off a fire or
- Do not use the Switch in locations where toxic gases, such as H2S, SO2, NH3, HNO3, and Cl2, may be present, or in locations subject to high temperature or humidity. Doing so may damage the Switch due to contact failure or corrosion.
- Do not let the Switch submerged in oil or water, or use in locations continuously subject to splashes of oil/water. Doing so may result in oil or water entering the Switch.
- Do not use the Switch in the following locations;
 - subject to severe temperature changes.
 - subject to high humidity or condensation.
 - subject to severe vibration or shock.
- where direct rays of the sun strike.
- where sea breeze may be present.
- When the Switch is exposed to the environment that are not required, or stored in locations where condensation presents, or damaged by fall out, or stored for more than an year, please test it under the usage conditions before application.
- Mounting and removing the Switch
 - 1. Insert the Operation Unit to the panel from the front. Install the lock ring and mounting nut from the terminal side and tighten the nut. Attach the Switch to the Operation Unit.
- 2. Align the lock ring with the groove in the casing, and insert it so that its edge is drawn to the panel side.
- 3. Tighten the nut to the torque of 0.98 to 1.96 N·m.
- 4. Snap on the Switch to the Operation Unit, aligning the arrow marks inscribed on both the Operation Unit and the Switch. Push the Switch into the Operation Unit until it clicks into place.
- 5. The push marks on both sides are only for detaching. Do not push them when you insert the Switch Unit to the Operation Unit. Otherwise, the Operation Unit is hooked wrongly.
- 6. To remove the Switch, push to move the levers on both sides in the direction indicated by PUSH mark. Applying too much holding force may damage the Switch.
- Wiring
 - 1. Do not wire the Switch while power is being supplied. Doing so may result in electric shock.
 - 2. Make sure to insert the connector to the end. This may prevent the Switch from functioning to its full capability.
 - 3. Do not subject the Switch to an excessive force when wiring. Fix the cables first to avoid the connector and cables from being pulled with. Otherwise, the connector may be disassembled or damaged, resulting in the contact damages.

Too much tension to the cables





4. Refer to specification of each connector or catalogue for details of installing or wiring the terminal side of the connector.


Recommended connector;

	Manufacture	Name	Model	Applicable lead wire
		Contact	SPHD-002T-P0.5	AWG#26 to 22
J.S.T. Mfg Co.	Contact	SPHD-001T-P0.5	AWG#28 to 24	
	Housing	PAP-10V-S	AWG#28 to 22	


· Choose the applicable contact to the wire.

Precautions for Correct Use

- Operating Environment
 - 1. This Switch is intended for indoor use only. Do not use the Switch outdoors.
 - 2. Do not set the Switch in locations where powders, mud, or any other substances may be piled, or subject to any splashes of oil or water. Always test the switch under actual working conditions before application.
- · Mounting panels
 - 1. Set mounting panel thickness to be 0.8 to 3.2 mm.
 - 2. The panel dimension is set as below;
 - The value in () indicated below is the minimum value suggested for easy detaching of the Switch.
 - Minimum panel pitch is 30/32 mm. Consider the flexibility and allowance of detaching and wiring, set the pitch to the appropriate value.



- Leave some spaces for a finger between panels, so as to pinch the levers
- Place the panels in the same direction. Do not set the connectors face to face for easy removal.



cannot be pushed

Some rooms for fingers to push.

Terms and Conditions of Sale

- Offer; Acceptance. These terms and conditions (these "Terms") are deemed part of all quotes, agreements, purchase orders, acknowledgments, price lists, catalogs, manuals, brochures and other documents, whether electronic or in catalogs, manuals, brochures and other documents, whether electronic or in writing, relating to the sale of products or services (collectively, the "Products") by Omron Electronics LLC and its subsidiary companies ("Omron"). Omron objects to any terms or conditions proposed in Buyer's purchase order or other documents which are inconsistent with, or in addition to, these Terms. Prices: Payment Terms. All prices stated are current, subject to change without notice by Omron. Omron reserves the right to increase or decrease prices on any unshipped portions of outstanding orders. Payments for Products are due net 30 days unless otherwise stated in the invoice. Discounts. Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only if (i) the invoice is paid according to Omron's payment terms and (ii) Buyer has no past due amounts.

- and (ii) Buyer has no past due amounts.

 Interest. Omron, at its option, may charge Buyer 1-1/2% interest per month or the maximum legal rate, whichever is less, on any balance not paid within the
- Orders. Omron will accept no order less than \$200 net billing.

 Governmental Approvals. Buyer shall be responsible for, and shall bear all costs involved in, obtaining any government approvals required for the importation or sale of the Products.
- Taxes. All taxes, duties and other governmental charges (other than general real property and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Omron or required to be collected directly or indirectly by Omron for the manufacture, production, sale, delivery, importation, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Omron.

 Financial. If the financial position of Buyer at any time becomes unsatisfactory
- <u>Financial</u>. If the financial position of Buyer at any time becomes unsatisfactory to Omron, Omron reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise comply with these Terms or any related agreement, Omron may (without liability and in addition to other remedies) cancel any unshipped portion of Products sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid accounts. unpaid accounts
- Cancellation: Etc. Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Omron against all related costs or expenses.

 10. Force Majeure. Omron shall not be liable for any delay or failure in delivery
- resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots, delay in or lack of transportation or the requirements of any government authority.

 11. Shipping: Delivery. Unless otherwise expressly agreed in writing by Omron:
 a. Shipments shall be by a carrier selected by Omron; Omron will not drop ship
- - except in "break down" situations.
 b. Such carrier shall act as the agent of Buyer and delivery to such carrier shall
- constitute delivery to Buyer; c. All sales and shipments of Products shall be FOB shipping point (unless oth- c. All sales and shipments of Products shall be FOB shipping point (unless otherwise stated in writing by Omron), at which point title and risk of loss shall pass from Omron to Buyer; provided that Omron shall retain a security interest in the Products until the full purchase price is paid;
 d. Delivery and shipping dates are estimates only; and
 e. Omron will package Products as it deems proper for protection against normal handling and extra charges apply to special conditions.

 12. Claims. Any claim by Buyer against Omron for shortage or damage to the Products occurring before delivery to the carrier must be presented in writing to Omron within 30 days of receipt of shipment and include the original transportation bill signed by the carrier noting that the carrier received the Products.
- portation bill signed by the carrier noting that the carrier received the Products from Omron in the condition claimed.
- Warranties. (a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.

 (b) <u>Limitations</u>. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABIL-

- ITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by tion, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty. See http://www.omron247.com or contact your Omron representative for published information.
- lished information.

 Limitation on Liability: Etc. OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY. Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.
- Indemnities. Buyer shall indemnify and hold harmless Omron Companies and their employees from and against all liabilities, losses, claims, costs and expenses (including attorney's fees and expenses) related to any claim, investigation, litigation or proceeding (whether or not Omron is a party) which arises or is alleged to arise from Buyer's acts or omissions under these Terms or in any way with respect to the Products. Without limiting the foregoing, Buyer (at its own expense) shall indemnify and hold harmless Omron and defend or settle any action brought against such Companies to the extent based on a claim that any Product made to Buyer specifications infringed intellectual property rights of another party.
- rights of another party.

 <u>Property: Confidentiality.</u> Any intellectual property in the Products is the exclusive property of Omron Companies and Buyer shall not attempt to duplicate it in any way without the written permission of Omron. Notwithstanding any charges to Buyer for engineering or tooling, all engineering and tooling shall remain the exclusive property of Omron. All information and materials supplied by Omron to Buyer relating to the Products are confidential and proprietary, and Buyer shall limit distribution thereof to its trusted employees and strictly prevent disclosure to any third party.
- prevent disclosure to any third party.

 <u>Export Controls.</u> Buyer shall comply with all applicable laws, regulations and licenses regarding (i) export of products or information; (iii) sale of products to "forbidden" or other proscribed persons; and (ii) disclosure to non-citizens of
- "forbidden" or other proscribed persons; and (ii) disclosure to non-citizens of regulated technology or information.

 Miscellaneous. (a) Waiver. No failure or delay by Omron in exercising any right and no course of dealing between Buyer and Omron shall operate as a waiver of rights by Omron. (b) Assignment. Buyer may not assign its rights hereunder without Omron's written consent. (c) Law. These Terms are governed by the law of the jurisdiction of the home office of the Omron company from which Buyer is purchasing the Products (without regard to conflict of law principles). (d) Amendment. These Terms constitute the entire agreement between Buyer and Omron relating to the Products, and no provision may be changed or waived unless in writing signed by the parties. (e) Severability If any provior waived unless in writing signed by the parties. (e) <u>Severability</u> If any provision hereof is rendered ineffective or invalid, such provision shall not invalidate any other provision. (f) Setoff. Buyer shall have no right to set off any amounts against the amount owing in respect of this invoice. (g) <u>Definitions</u>. As used herein, "<u>including</u>" means "including without limitation"; and "<u>Omron Companies</u>" (or similar words) mean Omron Corporation and any direct or indirect subsidiary or affiliate thereof.

Certain Precautions on Specifications and Use

- Suitability of Use. Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request. Omron will provide application of use of the Product. At Buyer's lequest, omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases but the following is a non-exhaustive list of applications for which particular attention must be given:

 (i) Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.

 (ii) Use in consumer products or any use in significant quantities.

 (iii) Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject and industrial consumers and consumers are consumers and status of the consumers and consumers.
 - ment, and installations subject to separate industry or government regulations. (iv) Systems, machines and equipment that could present a risk to life or prop erty. Please know and observe all prohibitions of use applicable to this Prod-
 - NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO

- ADDRESS THE RISKS, AND THAT THE OMRON'S PRODUCT IS PROP-ERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.
- Programmable Products. Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof. Performance Data. Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requires ments. Actual performance is subject to the Omron's Warranty and Limitations
- Change in Specifications. Product specifications and accessories may be change in specifications. Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time
- to confirm actual specifications of purchased Product.

 <u>Errors and Omissions.</u> Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.



OMRON INDUSTRIAL AUTOMATION • THE AMERICAS HEADQUARTERS

Schaumburg, IL USA • 847.843.7900 • 800.556.6766 • www.omron247.com

OMRON CANADA, INC. • HEAD OFFICE

Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • www.omron247.com

OMRON ELECTRONICS DE MEXICO • HEAD OFFICE

México DF • 52.55.59.01.43.00 • 001.800.556.6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE

Apodaca, N.L. • 52.81.11.56.99.20 • 001.800.556.6766 • mela@omron.com

OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE

São Paulo, SP, Brasil • 55.11.2101.6300 • www.omron.com.br

OMRON ARGENTINA • SALES OFFICE

Cono Sur • 54.11.4783.5300

OMRON CHILE • SALES OFFICE

Santiago • 56.9.9917.3920

OTHER OMRON LATIN AMERICA SALES

54.11.4783.5300

OMRON EUROPE B.V. • Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. • Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 88 • www.industrial.omron.eu